



~ .	LMBM36SL200
~ /	
fi fl Ł ĩ	1/2.8" Ž ž SONY Starvis! " # CMOS fi fl Ł
\$ % & ' (200) ĩ * 1080P
fi fl Ł + , ĩ *	1945(H)*1097(V)
- . / 0 ~ #	H.264/H.264+/H.265/H.265+/JPEG/AVI
1 . 2 3	PAL/NTSC
4 5 6 7	8 9 : PAL 1/25-1/10000Sec NTSC 1/25-1/10000Sec
\$: " ;	0.005Lux
1 < =	52dB
> ? @ #	A B > ?
- . C D	E F G H
I J K L	\
MN	
MN O P	/ Q ~ MN 2.8mm/F2.0
R O @ #	S O
MN ĩ	S O MN
ĩ *	300) T U MN
V -	
WX Y ` Z	/
\$ % WX P [/
WX \] ^ _	/
WX \] @ #	/
G H	
G H ` a	RJ-45 (10/100Mb c G a)
d e fi C	/
` f g h	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
G H i j	k l ONVIF 2.4
P2P	k l m n O
POEo 4	p q , k l IEEE 802.3af
- . r s	0.3t
u O v 1	2048° 1536@ 15fps
u O v 2	1920° 1080@ 30fps

u 0 v 3	1280*720@30fps
5 0 v 1	720*480@15fps 720*480@30fps
5 0 v 2	/
5 0 v 3	/
w 0 v	352*288@15fps 352*288@30fps
x y k	k l IEB-11, Google Chrome (: z Ver44), Firefox (: z Ver53), Mac Safari(: z version 12)
{ } /	k l iPhone, iPad, Android, Android Pad
` / ~	
€ V , #	8 9 f ,
... i t ‡	^ %& /S ; /k = ; /CE; ,Ml , 3D NR, ' ' " , FLK(" • - —)
™	/
\$ > , #	/
œ Ÿ , #	k l
ROI fl c E □ ¥	k l
! ™ § "	k l
T 9 © ^ «	/
- 9 ©	- 9 © : 96dB
- 9 ® ^	k l
° ± ² ³	3` μ ¶ □ ¥
. i , #	NVR/CMS/Web/SD Card
. 1	° » ¼ ½ ¾ ¿ » ¼ ½ ¾ Ž ½ ¾ À Á Â Ã Ä Å Æ Ç È É Ê Ë Ì Í Î Ï Ñ Ò Ó Ô Õ Ö × % À ½ ¾ Ø Å ½ ¾ Ù Ú ½ ¾ Û Ü ½
` a	
Ÿ .	p B Ÿ .
à á	1E à à à C f
SD à ä	\$ % k l 512GB
RS485 a	/
â	
/ æ ç è	é ê
k è	/
IR-CUT P i ™	/
ï ï ð ;	-20ñ ~ +60ñ RH95% Max
ò ó ò ;	-20ñ ~ +60ñ RH95% Max
4 ó ~	DC12V±10%, 500mA
õ ž	36(W) x 36(H) x 33(D)mm
ö Z	300g