



	LMDES600
	1/2.9" SONY CMOS
	400
	3096 (H) × 2202 (V)
	H.264/H.264+/H.265/H.265+/JPEG/AVI
	PAL/NTSC
	: PAL 1/25-1/10000Sec. NTSC 1/25-1/10000Sec
	0.01Lux
	52dB
	cvbs
	1.05mm
	500
	42μx 3
	20
	10Lux CDS
	CDS
	RJ-45 (10/100M)
	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
	ONVIF 2.4
P2P	
POE	, IEEE 802.3af
	0.3
1	2048° 2048@ 20fps
2	1536° 1536@ 30fps

3	1024*1024@ 30fps
1	720*720@ 20fps 720*720@ 30fps
2	/
3	/
	512*512@ 20fps 512*512@ 30fps
	IE9-11, Google Chrome(Ver 45), Firefox(Ver 53), Mac Safari
	iPhone, iPad, Android, Android Pad
	3dbi
	/
Wi-Fi	Wi-Fi(IEEE802.11b/g/n),2.4Ghz
WIFI	300
	IR-CUT
	/ / / , 3D NR, , FLK()
	/
ROI	/
	/
	: 50dB
	3
	NVR/VMS/Web/SD Card
	(3.5mm)
	1 /
SD	SD 128G Micro SD
RS485	/
	: , :
	/
IR-CUT	
	-20 ~ +60 RH95% Max
	-20 ~ +60 RH95% Max
	DC12V±10%, 950mA
	120 x 49(H) mm
	500g